



**SCHNEIDER UNITATE RACIRE CONECTABILA, MONTAJ PE LATERALUL
DULAPULUI, CLIMASYS CU, 2KW, 3 POLI, 380/460V, 50/60HZ, IP55**

Gama: ClimaSys
nume produs: CU
Suport de montare: Lateral
Tip produs sau componenta: Cooling unit
Installation: Interior lateral
destinatie produs: Pentru carcasa
mod de montare: Cu suruburi
Supply Voltage: 380...415 V 3 faze 50 Hz EN/IEC
400/460 V +/- 6 % 3 faze 60 Hz UL
Rated Power: 2000 W
putere de racire: 2000 W 50/60 Hz L35-L35
1900 W 50/60 Hz L35-L50
inaltime: 1000 mm
latime: 405 mm
adancime: 225 mm
[In] curent nominal: 2,5 A
curentul de varf: 13 A
puterea consumata in W: 900 W la 50/60 Hz, L35-L35
1000 W la 50/60 Hz, L35-L50
raportul de eficienta energetica: 2,2
tip de control: Controler electronic
gama de setare a temperaturii: 20...50 °C la 50/60 Hz
temperatura ambientala de utilizare: In cofret 20...50 °C la 50/60 Hz
Outside the enclosure 5...55 °C la 50/60 Hz
Noise level: 72 dB
presiune: 30 bar

Flow rate: Internal circuit 850 m³/h la 50/60 Hz

External circuit 1200 m³/h la 50/60 Hz

greutate neta: 40,4 kg

tip de gaz de racire: R134a (0,390 kg)

Type of filter: Optional external circuit filter

Recommended circuit breaker protection: M9F23316

Thermal protection Recommended (fuse): 3 faze 15 A (T)

material: Otel

culoare: Gri (RAL 7035)

certificari produs: UL

IEC

EN

directive: 2006/42/EC - machinery

2014/30/EU - directiva de compatibilitate electromagnetica

2011/65/EU - RoHS

standarde: EN/ISO 12100

EN 60335-1

EN 60335-2-40

EN 61000-3-2

EN 61000-3-3

EN 61000-6-2

EN 61000-6-3

SR EN IEC 63000:2019

EN 14511

grad de protectie IP: IP55 conformitate cu SR EN 60529 (on the internal circuit)

IP24 conformitate cu SR EN 60529 (on the external circuit)

Pret: 18.492,81 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/unitate-racire-conectabila-montaj-pe-lateralul-dulapului-climasys-cu-2kw-3-poli-380-460v-50-60hz-ip55>