



## SCHNEIDER MODUL ETHERNET PENTRU M580 - 3 PORTURI DE COMUNICATIE ETHERNET

gama de produse: Modicon M580

Tip produs sau componenta: Modul de comunicatie

aplicatie a dispozitivului: Process and control communication module

compatibilitate produs: Modicon M580 standalone CPU (BMEP58.....)

Modicon M580 Redundant CPU (BMEH58.....)

Modicon M580 safety CPU (non interfering type 1) (BMEP582.....)

Modicon M580 safety Redundant CPU (non interfering type 1) (BMEH582.....)

Modicon X80 Rack with Ethernet backplane (BMEXBP.....)

locul de montare: Main rack

Backplane slot location: Ethernet + X-bus Slot

Slot occupied by module: 1

Maximum number of modules per rack: 4

alimentare: Alimentare electrica interna prin rastele

tip de conexiune integrata: 3 Ethernet, tip conector: RJ45, rata de transmisie: 10/100 Mbit/s, mod de transmisie: Ecranat si dublu torsadat

mediu de sustinere a transmisiei: Rack cu Ethernet

serviciu de comunicare: Managementul l?imii de band?

Server FDR

Administrator de retea SNMP

Modbus TCP I/O Scanner and Messaging

Ethernet/IP I/O Scanner and Messaging

RSTP support

Port mirroring

Switch multiport inclus

server Web: For commissioning, operational and maintenance

consum de curent: 900 mA la Tensiune alimentare 3.3V c.c. (for product version >= 13)

1800 mA la Tensiune alimentare 3.3V c.c. (for product version < 13)

semnalizare locala: 1 LED (verde) for functionare procesor (RUN)

1 LED (rosu) for defect procesor sau sistem(ERR)

1 LED (verde/rosu) for ETH MS (Status configurare port Ethernet)

1 LED (verde/rosu) for Eth NS (Status retea Ethernet)

latime: 32 mm

inaltime: 103,7 mm

lungime: 86 mm

greutate neta: 0,2 kg

grad de protectie IP: IP20

temperatura ambientala de functionare: 0...60 °C

marcaj: CE

directive: 2014/35/EU - directiva joasa tensiune

2014/30/EU - directiva de compatibilitate electromagnetica

Pret: 5.445,81 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/modul-ethernet-pentru-m580-3-porturi-de-comunicatie-ethernet>