

# SCHNEIDER BAZA PENTRU INTRERUPATOR DE SARCINA VARIO - 3 POLI - 12 A

Gama: TeSys
numele produsului: TeSys VARIO
referinta produs: V
Tip produs: Corp de comutator
Suport de montare: Placa
?in? simetric?
Performance Level: Performante ridicate
Poli: 3P
Contact Type and Composition: 3 NO
Tipul retelei: C.a.
C.c.
Frecventa retelei: 50/60 Hz
[Ue] IEC Rated Operational Voltage: 690 V c.a. 50/60 Hz
IEC Rated Operational Power in W: 3 kW la 400...415 V (AC-3)
4 kW la 500 V (AC-3)
1,5 kW la 230...240 V (AC-3)
5,5 kW la 500 V (AC-23A)
5,5 kW la 690 V (AC-3)
7,5 kW la 690 V (AC-23A)
3 kW la 230...240 V (AC-23A)
4 kW la 400...415 V (AC-23A)
[Ie] Rated Operational Current: 8,1 A AC-23 Ue: 400 V
[Ith] Conventional Free Air Thermal Current: 12 A
[Ithe] Conventional Enclosed Thermal Current: 10 A
Making capacity ( I Rms): 120 A la 400 V AC-21A
120 A la 400 V AC-22A
120 A la 400 V AC-23A

Breaking Capacity: 120 A la 400 V (AC-21A)
120 A la 400 V (AC-22A)
120 A la 400 V (AC-23A)
Rated Conditional Short Circuit Current: 10 kA la 400 V - siguranta asociata 12 A aM
10 kA la 400 V - siguranta asociata 12 A gG
[Icm] Rated Short Circuit Making Capacity: 1 kA la 400 V la varf
Clasa de functionare intermitenta: 30
Suitability for isolation: Da
[Uimp] rated impulse withstand voltage: 8 kV
[Icw] rated short-time withstand Rms current: 300 A la 400 V durata: 1 s
Durabilitate mecanica: 100000 cic
Electrical Durability: 100000 cic AC-21
30000 cic DC-1
30000 cic DC-2
30000 cic DC-3
30000 cic DC-4
30000 cic DC-5
IEC Terminal Connection: Circuit de alimentare borne cu surub cablu 10 mm² - rigiditate cablu: solid
Circuit de alimentare borne cu surub cablu 6 mm² - rigiditate cablu: flexibil - cu pini
Cuplu de strangere: Circuit de alimentare 2,1 N.m - pornit borne cu surub
Inaltime: 74 mm
Latime: 55 mm
Adancime: 60 mm
greutatea produsului: 0,2 kg
Standarde: SR EN 60947-3
Certificari de produs: UL
CSA
GL
UKCA
CCC
Grad de protectie: IP20 conforming to SR EN 60529
Protective Treatment: TC
Mechanical Robustness: Vibra?ii 10...150 Hz (1 gn) conformitate cu IEC 60068-2-6
?ocuri 11 ms (30 Gn) conformitate cu IEC 60068-2-27
temperatura aerului ambiant pentru functionare: -20…50 °C
Fire Resistance: 960 °C conformitate cu IEC 60695-2-1
Pret: 71,84 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/baza-pentru-intrerupator-de-sarcina-vario-3-poli-12-a