



**SCHNEIDER UNITATE RACIRE CONECTABILA, MONTAJ PE LATERALUL
DULAPULUI, CLIMASYS CU, 3.2KW, 3 POLI, 380/460V, 50/60HZ, IP55**

Gama: ClimaSys

nume produs: CU

Suport de montare: Lateral

Tip produs sau componenta: Cooling unit

Installation: Interior lateral

destinatie produs: Pentru carcasa

mod de montare: Cu suruburi

Supply Voltage: 380...415 V 3 faze 50 Hz EN/IEC

400/460 V +/- 6 % 3 faze 60 Hz UL

Rated Power: 3200 W

putere de racire: 3200 W 50/60 Hz L35-L35

2600 W 50/60 Hz L35-L50

inaltime: 1300 mm

latime: 490 mm

adancime: 250 mm

[In] curent nominal: 3,5 A

curentul de varf: 20 A

puterea consumata in W: 1200 W la 50/60 Hz, L35-L35

1400 W la 50/60 Hz, L35-L50

raportul de eficienta energetica: 2,6

tip de control: Controler electronic

gama de setare a temperaturii: 20...50 °C la 50/60 Hz

temperatura ambientala de utilizare: In cofret 20...50 °C la 50/60 Hz

Outside the enclosure 5...55 °C la 50/60 Hz

Noise level: 72 dB

presiune: 32 bar

Flow rate: Internal circuit 1200 m³/h la 50/60 Hz
External circuit 1400 m³/h la 50/60 Hz
greutate neta: 58,9 kg
tip de gaz de racire: R134a (0,482 kg)
Type of filter: Optional external circuit filter
Recommended circuit breaker protection: M9F23316
Thermal protection Recommended (fuse): 3 faze 15 A (T)
material: Otel
culoare: Gri (RAL 7035)
certificari produs: UL
IEC
EN
directive: 2006/42/EC - machinery
2014/30/EU - directiva de compatibilitate electromagnetica
2011/65/EU - RoHS
standarde: EN/ISO 12100
EN 60335-1
EN 60335-2-40
EN 61000-3-2
EN 61000-3-3
EN 61000-6-2
EN 61000-6-3
SR EN IEC 63000:2019
EN 14511
grad de protectie IP: IP55 conformitate cu SR EN 60529 (on the internal circuit)
IP24 conformitate cu SR EN 60529 (on the external circuit)
Pret: 23.226,10 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/unitate-racire-conectabila-montaj-pe-lateralul-dulapului-climasys-cu-3-2kw-3-poli-380-460v-50-60hz-ip55>