



SCHNEIDER SPACELOGIC, SERVER DE AUTOMATIZARE AS-P-3 V3 PREMIUM

gama de produse: SpaceLogic

Tip produs sau componenta: Controller

versiune software: \geq V7.0

Gama: SpaceLogic

certificari produs: RCM

UE

FCC Class B

WEEE

UKCA

cULus

ICES-003

ACMA

UL/cUL 916

abatere ceas: \pm 52 s/month

culoare: Negru

serviciu de comunicare: SNMP network management

Notificare prin e-mail SMTP

SMTSPS e-mail notification

Modbus TCP client

Modbus TCP server

DHCP

DNS client

NTP synchronization

consum de curent: $<$ 2.5 A

nume scurt al dispozitivului: AS-P-3

Rezistenta la foc: UL94 V-0

numar maxim de module de expansiune I/O: 29

puterea maxima consumata in W: 40 W
grad de protectie IP: IP20
mod de montare: DIN rail mount
adancime: 64 mm
inaltime: 114 mm
greutate neta: 0,550 kg
latime: 180 mm
temperatura ambientala de functionare: 0...55 °C
temperatura ambietala pentru depozitare: -20...70 °C
tip memorie: 2 GB RAM LPDDR4
32 GB flash
Standarde: FCC Partea 15 clasa B
ICES-003
CE
UL 916
RoHS
Gama: SpaceLogic
marca de produs: Schneider Electric
nume produs: SpaceLogic Automation Svr AS-P-3
Processor requirement: ARM Cortex-A72 dual-core
capacitate procesor I/O limitator: 464 I/O, 29 modules
material: ABS/PC
montare produs: Sina DIN
servicii Web: TLS1.3
HTTP server
HTTPS server
tip de conexiune integrata: USB 3.0 type C
USB 2.0 tip A
Ethernet
RS485
nume procesor: ARM Cortex-A7 dual core at 2000 MHz
Compatibilitate gama: SpaceLogic AS-P-3-CONN connector kit
protocol port de comunicare: BACnet IP RJ45
BACnet MS/TP RS485
BACnet SC RJ45
Modbus TCP RJ45
Modbus RTU RS485
HTTPS RJ45
HTTP RJ45
OPC UA client RJ45
umiditate relativa: 0...95 %
Pret: 5.083,22 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/spacelogic-server-de-automatizare-as-p-3-v3-premium>