

SCHNEIDER BAZA PENTRU INTRERUPATOR DE SARCINA VARIO - 3 POLI - 175 A

Gama: TeSys
numele produsului: TeSys VARIO
referinta produs: V
Tip produs: Corp de comutator
Suport de montare: ?in? simetric?
Placa
Performance Level: Performante ridicate
Poli: 3P
Contact Type and Composition: 3 NO
Tipul retelei: C.a.
C.c.
Frecventa retelei: 50/60 Hz
[Ue] IEC Rated Operational Voltage: 690 V c.a. 50/60 Hz
IEC Rated Operational Power in W: 30 kW la 230...240 V (AC-3)
37 kW la 400...415 V (AC-3)
37 kW la 690 V (AC-3)
45 kW la 500 V (AC-3)
45 kW la 690 V (AC-23A)
55 kW la 500 V (AC-23A)
30 kW la 230...240 V (AC-23A)
45 kW la 400...415 V (AC-23A)
[Ie] Rated Operational Current: 83 A AC-23 Ue: 400 V
[Ith] Conventional Free Air Thermal Current: 175 A
[Ithe] Conventional Enclosed Thermal Current: 140 A
Making capacity (I Rms): 1750 A la 400 V AC-22A
1750 A la 400 V AC-23A
1600 A la 400 V AC-21A

Breaking Capacity: 1400 A la 400 V (AC-21A)
1400 A la 400 V (AC-22A)
1400 A la 400 V (AC-23A)
Rated Conditional Short Circuit Current: 10 kA la 400 V - siguranta asociata 200 A aM
10 kA la 400 V - siguranta asociata 200 A gG
[Icm] Rated Short Circuit Making Capacity: 2,8 kA la 400 V la varf
Clasa de functionare intermitenta: 30
Suitability for isolation: Da
[Uimp] rated impulse withstand voltage: 8 kV
[Icw] rated short-time withstand Rms current: 2100 A la 400 V durata: 1 s
Durabilitate mecanica: 30000 cic
Electrical Durability: 30000 cic AC-21
30000 cic DC-1...5
IEC Terminal Connection: Circuit de alimentare borne cu surub cablu 70 mm² - rigiditate cablu: flexibil - cu pini
Circuit de alimentare borne cu surub cablu 95 mm² - rigiditate cablu: solid
Cuplu de strangere: Circuit de alimentare 22,6 N.m - pornit borne cu surub
Inaltime: 125 mm
Latime: 90 mm
Adancime: 90 mm
greutatea produsului: 0,9 kg
Standarde: SR EN 60947-3
Certificari de produs: UL
CSA
GL
UKCA
Grad de protectie: IP20 conforming to SR EN 60529
Protective Treatment: TC
Mechanical Robustness: Vibra?ii 10...150 Hz (1 gn) conformitate cu IEC 60068-2-6
?ocuri 11 ms (30 Gn) conformitate cu IEC 60068-2-27
temperatura aerului ambiant pentru functionare: -20…50 °C
Fire Resistance: 960 °C conformitate cu IEC 60695-2-1
Pret: 835,28 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/baza-pentru-intrerupator-de-sarcina-vario-3-poli-175-a