
Image not found or type



LEDVANCE DISPOZITIV DE CONTROL ILUMINAT LEDVANCE (OSRAM) DALIECO BT RTC CONTROL, 230 V, IP20

Beneficii produs Daytime depending change of brightness and color temperature (HCL) Suitable for Human Centric Lighting Applications (HCL) Control the light via Smartphone Adjustment of all settings via smartphone Up to 4 timers with ON-/OFF-Time and weekday configurable Simplified startup thanks to predefined operation modes Intuitive manual dimming, switching and changing of colour temperature Up to 4 groups separatly controllable Adjustable Offset for different groups Easy Scene creation via App Scene-recall via OSRAM DALI PRO PB coupler possible Firmware update over-the-air via Bluetooth possible Integrated DALI supply Control of standard white or Tunable White light acc. DALI device type 8 (DT8)* Selected DALI parameters changeable via APP Zone de utilizare Floor-standing luminaires Offices Conference rooms Training rooms Classrooms Corridors Shop lighting Caracteristici produs Compact light control with DALI interface Smart phone connection via Bluetooth to control and configure Integrated clock for time based control of brightness and color temperature (HCL) Adaptable HCL curve with up to 24 points One DALI output channel (Broadcast or Groupcast) Up to 32 DALI luminaires connectable Supports up to 4 OSRAM DALI sensors and pushbutton couplers Daylight-dependent regulation and presence-dependent control of light Pushbutton interface to separately control brightness and color temperature Supports DALI DT8 Tunable White driver Outputs with electronical reversible overtemperature, short-circuit, overload protection Length of the DALI control cable: up to 300 m Length of the pushbutton cable: up to 50 m Suitable for luminaire integration Echipamente / Accesorii Free App for iOS and Android available at the app store Ceiling or independent installation via ECO CI KIT possible DATE ELECTRICE
Putere nominala 3,00 W
Tensiune nominala 230 V
Frecventa retea 50/60 Hz
Dimensiuni si greutate
Lungime 108,00 mm
Latime 30.00 mm
inaltime 21.00 mm
Greutate produs 45,00 g

Temperaturi si conditii de functionare
Intervalul temperaturii ambientale -20…+60 °C
DATE SUPLIMENTARE REFERITOARE LA PRODUS
Numar de iesiri de control 1
Numar de senzori ce se pot conecta 4
Max. cuplaje/senzori cu butoane ce se pot conecta 4
Punerea in functiune a aplicatiei App (Android/ iOS)
Grupuri 4
Capacitati
Reglabil (cu posibilitate de diminuare a intensitatii luminoase) Nu
Interfata de diminuare a intensitatii luminoase DALI
Tip de instalare Integrarea corpului de iluminat/Montare independenta
Intervalul transmitatorului 15 m
CERTIFICATE sI STANDARDE
Marci de omologare – aprobare CE
Clasa de protectie II
Tip de protectie IP20
Clasa de eficienta energetica None
FIsa DE PRODUS PRIVIND CARACTERISTICILE sI PERFORMANtELE DE MEDIU
Cantitatea de metale pretioase 0 mg
Cantitatea de pamanturi rare 0 mg
Rata minima de material reciclat din ambalaj 80 % 1)
Procentul minim de continut reciclat din produs 0 % 1)
Reciclabilitatea produsului Produs in mare parte reciclabil 1)
Caracterul reciclabil al ambalajului Ambalaje in mare parte reciclabile 1)
Lista substantelor periculoase cuprinse in produs in concentratii mai mari de 0,1% in procent de masa Nu
Contine substante care prezinta motive de ingrijorare deosebita in concentratii mai mari de 0,1% in procent de masa Da
Lista substantelor care prezinta motive de ingrijorare deosebita in concentratii mai mari de 0,1% in procente masice Lead (7439-92-1)
1) in conformitate cu Decretul AGEC 2022-748 (Legislatia franceza impotriva deseurilor pentru o economie circulara)
Pret: 674,99 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/dispozitiv-de-control-iluminat-ledvance-osram-dalieco-bt-rtc-control-230-v-ip20