Image not found or type



LEDVANCE CORP DE ILUMINAT LED ETAN? LEDVANCE DP DA 5TH 1500 P 61 W 840 VW IP66, 11000 LM, 4000 K, 110°, DIMABIL

Beneficii produs Corp de iluminat adecvat pentru sistemele de management al luminii DALI-2 Driver adecvat pentru sistemele de iluminat de evacuare de urgenta conform EN 50172 Lumina distribuita uniform Economii de energie de pana la 70 % (fata de corpurile de iluminat cu lampi fluorescente) Instalare simpla, nu este nevoie de scule pentru racordare Foarte versatil datorita treptelor de flux luminos selectabile (Multi Select) prin comutatoarele de pe driver Nivel scazut al licaririi ? 5 % Good glare reduction (UGR < 25) up to 8000 lm 26 cm installation range for flexible mounting bracket positioning Permite participarea la programe de finantare in anumite tari pentru inlocuirea sursei de lumina si a driverului Garantie 7 ani Zone de utilizare Instalatii DALI Unitati industriale si de depozitare Parcari si pasaje subterane Garaje Ateliere, linii de asamblare Suitable for indoor and sheltered outdoor areas Caracteristici produs Cablaj de trecere 5x2,5mm² deja instalat Very high luminous efficacy: up to 180 lm/W Very long lifetime (L80): up to 100,000 h (at 25 °C) Clasificare IP66 si IK10 Temperatura ambianta in timpul functionarii: -20…+40 °C Uniformitatea culorii: ? 3 SDCM Disponibil cu 3 lungimi diferite: 600 mm, 1200 mm si 1500 mm Available in 3000 K, 4000 K and 6500 K Carcasa rezistenta din policarbonat UV-stabilized Unghiul fasciculului: 110° Echipamente / Accesorii Cleme din otel inoxidabil cu suruburi de siguranta incluse Mounting accessories included (suspension kit, theft protection kit, 2nd cable gland and 2 grommets) Recomandari privind siguranta Toate conexiunile electrice trebuie efectuate de o persoana calificata. Atentie, risc de electrocutare. Produs cu clasa de protectie I. Toate componentele metalice conductoare de electricitate ale carcasei care pot absorbi tensiune in timpul functionarii sau in timpul intretinerii in cazul unei defectiuni trebuie conectate continuu la conductorul de impamantare de protectie. Referinte / Linkuri Pentru Garantie, consultati www.ledvance.com/guarantee DATE ELECTRICE
Putere nominala 61 W
Tensiune nominala 220…240 V
Frecventa retea 0/50/60 Hz
Curent nominal 275 mA
soc de curent la anclansare 26 A
Timp soc de curent la anclansare T h50 95 µs

Max. no. of lum. on circuit break. B16 A 27
Nr. max. de aparate de iluminat pe disjunctor C10 A 23
Max. no. of lum. on circuit break. C16 A 36
Factor de putere ? > 0,90
Distorsiune armonica totala < 15 %
Clasa de protectie I
Capacitate la supratensiune tranzitorie (L-N) 1 kV
Capacitate la supratensiune tranzitorie (L/N - impamantare) 2 kV
Mod de functionare Mecanism de actionare LED integrat
DATE FOTOMETRICE
Flux luminos 11000 lm
Eficacitate luminoasa 180 lm/W
Temperatura culorii 4000 K
Culoare lumina (denumire) Alb rece
Indice de redare a culorilor Ra > 80
Abatere standard a asocierii culorilor ?3 sdcm
Nivel scazut al licaririi Da
Parametru licarire (Pst LM) < 1
Parametru efect stroboscop (SVM) < 0.4
Grup de siguranta fotobiologica, conform EN62778 RG0
Unghiul fasciculului 110 °
Clasificare uniformizata pentru reflexie (UGR) < 25 1)
1) @ 8000 lm
Dimensiuni si greutate
Lungime 1500,00 mm
inaltime 68,00 mm
Latime 82,00 mm
Greutate produs 2037,00 g
MATERIALE sI CULORI
Culoare produs Gri
Culoarea carcasei Gri
Numar RAL RAL 9018
Material corp Policarbonat (PC)
Material de acoperire Policarbonat (PC)
Material de suprafata emitator de lumina Policarbonat (PC)
Testare bazata pe fire incandescente conform standardului IEC 60695-2-12 850 °C
Continut de mercur 0.0 mg
APLICARE sI MONTARE
Intervalul temperaturii ambientale -20…+40 °C
Interval de temperatura la depozitare -20…+80 °C
Tipul racordului Borna fara surub, 5 poli
Tip de protectie IP66
Clasa de protectie IK (rezistenta la socuri) IK10 1)
Reglabil (cu posibilitate de diminuare a intensitatii luminoase) Da
Tip de diminuare a intensitatii luminoase DALI-2
Pregatit pentru IoT Suport pentru tipurile de date DALI PART 251, 252, 253 2)
Tip de montare Aparent/Suspendat
Loc de montare Plafon; Perete
Mediu de utilizare Interior
Reglabil Nu
Cu sursa de lumina Da
Sursa de lumina inlocuibila Da
1) The IK10 rating applies only when all clips are fully secured with screws / otherwise, the luminaire will be rated as IK08

2) Internet of Things. Supports data transfer via gateway to cloud-based monitoring platforms, such as LEDVANCE VIVARES Cloud
Durata de viata
Durata de viata L70/B50 la 25 °C 120000 h 1)
Durata de viata L80/B10 la 25 °C 100000 h 1)
Durata de viata L90/B10 la 25 °C 60000 h
Numar de cicluri de comutare 120000
1) t[h]: L70/B50 la 25 °C (Ta), t[h]: L80/B10 la 25 °C (Ta), t[h]: L90/B10 la 25 °C (Ta)
DISPOZITIV DE CONTROL
Curent de iesire 205 mA
ECG - Curent de ondulatie la iesire < 5 %
ILUMINAT DE URGENta
Tipul de iluminat de urgenta (EL) Driver certificat EL (functionare 0Hz / DC) pentru functionare centrala cu baterie inclusa
Tip de test la functionare in regim de urgenta Nimic
CERTIFICATE sI STANDARDE
Standarde CE; CB; EAC; UKCA; ENEC
Corp de iluminat cu temperatura limitata la suprafata, „D sign” Da
Protectie la lovirea cu mingea Nu
Modul LED inlocuibil Exclusiv de un profesionist
DATE SUPLIMENTARE REFERITOARE LA PRODUS
Observatie cu privire la produs Available from September 2026; Cand este utilizat in aplicatii foarte reci, cum ar fi depozitarea la rece, poate fi necesara o membrana speciala pentru a asigura durata de viata
Functie adaugata VIVARES
FIsa DE PRODUS PRIVIND CARACTERISTICILE sI PERFORMANtELE DE MEDIU
Rata minima de material reciclat din ambalaj 80 % 1)
Procentul minim de continut reciclat din produs 0 % 1)
Reciclabilitatea produsului Produs in mare parte reciclabil 1)
Caracterul reciclabil al ambalajului Ambalaje in mare parte reciclabile 1)
Lista substantelor periculoase cuprinse in produs in concentratii mai mari de 0,1% in procent de masa Nu
Contine substante care prezinta motive de ingrijorare deosebita in concentratii mai mari de 0,1% in procent de masa Nu
1) in conformitate cu Decretul AGEC 2022-748 (Legislatia franceza impotriva deseurilor pentru o economie circulara)
Pret: 726,07 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/corp-de-iluminat-led-etans-ledvance-dp-da-5th-1500-p-61-w-840-vw-ip66-11000-lm-4000-k-110deg-dimabil