Image not found or type



LEDVANCE DRIVER LED LEDVANCE (OSRAM) OT 130/220-240/24 DIM P, 140,00 W, 220-240 V, IP66, DIMABIL

Beneficii produs Large range of products from 20 W to 250 W Installation in very cold and hot environments Very stable output power High electronical reversible short-circuit, overload, overtemperature protection Smart Power Supply: boosting power to turn on cold LEDs Independent installation possible Dimming range: 1…100 % Zone de utilizare Facades, public squares, cruise ships Signage Suitable for indoor and outdoor installations Caracteristici produs DC mode functionality Type of protection: IP66 and IP67 Surge protection: up to 4 kV (L-N) / 6 kV (L/N-PE) Wide operating temperature range: -30…+55 °C Lifetime: up to 50,000 h (temperature at max. t c) Dimmable via fully isolated 1…10 V interface DATE ELECTRICE
Putere nominala 140,00 W
Putere nominala de iesire 130 W
Tensiune nominala 220…240 V
Tensiune nominala de iesire 24,2 V
CA tensiune de intrare 198…264 V
CC tensiune de intrare 176…276 V
U-OUT (tensiune de lucru) 30 V
soc de curent la anclansare 60 A
Frecventa retea 0/60 Hz
Distorsiune armonica totala < 15 %
Factor de putere ? 0,95
Eficienta ECG 90,5 %
Pierdere de putere a dispozitivului 13,3 W
Nr. ECG max. pe disjunctor 10 A (B) 8
Nr. ECG max. pe disjunctor 16 A (B) 13
Nr. ECG max. pe disjunctor 25 A (B) 20
Capacitate la supratensiune tranzitorie (L/N - impamantare) 6 kV
Capacitate la supratensiune tranzitorie (L-N) 4 kV
Izolatie galvanica SELV

Pierdere de putere in mod stand by < 0.5 W
Dimensiuni si greutate
Lungime 220,00 mm
Distantare orificiu de montare, lungime 207 mm
Latime 63.00 mm
inaltime 37.00 mm
Sectiune transversala de cablu, partea de intrare 1 mm²
Sectiune transversala de cablu, partea de iesire 1 mm²
Lungimea de pregatire a cablului, partea de intrare 90 mm
Lungimea de pregatire a firului, partea de iesire 90 mm
Greutate produs 943,00 g
CULORI sI MATERIALE
Materialul carcasei Metal
Material corp Metal
Temperaturi si conditii de functionare
Intervalul temperaturii ambientale -30…+55 °C
Temperatura maxima in punctul de proba tc 80 °C
Temperatura max. a carcasei in caz de defectiune 110 °C
Umiditate relativa permisa pe durata functionarii 5…85 % 1)
1) Maxim 56 de zile/an la 85 %
Durata de viata
Durata de viata ECG 50000 h
DATE SUPLIMENTARE REFERITOARE LA PRODUS
Capsulat Da
Capacitati
Reglabil (cu posibilitate de diminuare a intensitatii luminoase) Da
Interfata de diminuare a intensitatii luminoase 1…10 V
Interval de diminuare a intensitatii luminoase 1…100 %
Protectie impotriva supraincalzirii Da
Protectie la supraincarcare Da
Protectie la scurtcircuit Da
Protectie la sarcina nula Da
Potrivit pentru aparate de iluminat cu clasa de protectie I
Tip de conectare, partea de iesire Cabluri
CERTIFICATE sI STANDARDE
Marci de omologare – aprobare ENEC; RCM; CCC; EAC
Standarde Conform EN 61347-1; Conform EN 61347-2-13; Conform EN 55015; Conform EN 61547; Conform EN 61000-3-2; Conform EN 61000-3-3; Conform EN 60598-1; Conform EN 62384
Clasa de protectie I
Tip de protectie IP66/IP67
Clasa de eficienta energetica None
DATE LOGISTICE
Interval de temperatura la depozitare -40…+85 °C
FIsa DE PRODUS PRIVIND CARACTERISTICILE sI PERFORMANtELE DE MEDIU
Cantitatea de metale pretioase 0 mg
Cantitatea de pamanturi rare 0 mg
Rata minima de material reciclat din ambalaj 80 % 1)
Procentul minim de continut reciclat din produs 0 % 1)
Reciclabilitatea produsului Produs in mare parte reciclabil 1)
Caracterul reciclabil al ambalajului Ambalaje in mare parte reciclabile 1)
Lista substantelor periculoase cuprinse in produs in concentratii mai mari de 0,1% in procent de masa Nu
Contine substante care prezinta motive de ingrijorare deosebita in concentratii mai mari de 0,1% in procent de masa Da
Lista substantelor care prezinta motive de ingrijorare deosebita in concentratii mai mari de 0,1% in procente

masice Lead (7439-92-1)
1) in conformitate cu Decretul AGEC 2022-748 (Legislatia franceza impotriva deseurilor pentru o economie circulara)
Pret: 505,24 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/driver-led-ledvance-osram-ot-130-220-240-24-dim-p-140-00-w-220-240-v-ip66-dimabil