Image not found or type



LEDVANCE DRIVER LED LEDVANCE (OSRAM) OT DMX RGBW DIM, 180,00 W, 12-24 V, IP20, DIMABIL

Beneficii produs 3- and 4-channel DMX dimmer for RGB and RGBW LED module Independent housing for ceiling installation High PWM frequency to optimize video recording Zone de utilizare Suitable for indoor installations Shops and hospitality: retail, hotels, restaurants Museums, residential buildings Caracteristici produs Intelligent DMX dimmer with multi-channel topology and single control Automatic or manual addressing Device fits also for special applications where dimming below 1 % is required DATE ELECTRICE
Putere nominala 180,00 W
Putere nominala de iesire 182 W
Tensiune nominala 12…24 V
Tensiune nominala de iesire 12…24 V
CC tensiune de intrare 12/24 V
U-OUT (tensiune de lucru) 24 V
Frecventa retea 0 Hz
Eficienta ECG 95 % 1)
Pierdere de putere a dispozitivului 4 W 2)
Izolatie galvanica Neizolat
Pierdere de putere in mod stand by < 0.5 W
1) La sarcina totala
2) Maxim
Dimensiuni si greutate
Lungime 172,00 mm
Distantare orificiu de montare, lungime 164,0 mm
Latime 42.00 mm
inaltime 20.00 mm
Sectiune transversala de cablu, partea de intrare 0.5…1.5 mm²
Sectiune transversala de cablu, partea de iesire 0.5…1.5 mm²

Lungimea de pregatire a cablului, partea de intrare 10 mm
Lungimea de pregatire a firului, partea de iesire 10 mm
Greutate produs 71,00 g
CULORI sI MATERIALE
Culoare produs Alb
Materialul carcasei Plastic
Material corp Plastic
Temperaturi si conditii de functionare
Intervalul temperaturii ambientale -20…+45 °C
Temperatura maxima in punctul de proba tc 65 °C
Temperatura max. a carcasei in caz de defectiune 115 °C
Umiditate relativa permisa pe durata functionarii 5…85 % 1)
1) Maxim 56 de zile/an la 85 %
Durata de viata
Durata de viata ECG 50000 h 1)
1) T c = 85°C, 0,2% / 1.000 h rata a defectarii
DATE SUPLIMENTARE REFERITOARE LA PRODUS
Capsulat Nu
Numar de iesiri de control 4
Capacitati
Reglabil (cu posibilitate de diminuare a intensitatii luminoase) Da
Interfata de diminuare a intensitatii luminoase DMX
Interval de diminuare a intensitatii luminoase 0…100 %
Protectie impotriva supraincalzirii Da
Protectie la supraincarcare Da
Protectie la scurtcircuit Da 1)
Protectie la sarcina nula Da
Potrivit pentru aparate de iluminat cu clasa de protectie I; II
Tip de conectare, partea de iesire Borna cu surub
Tip de instalare Integrarea corpului de iluminat/Integrare in plafon
1) impreuna cu sursa de alimentare electrica OPTOTRONIC
CERTIFICATE sI STANDARDE
Marci de omologare – aprobare CE; MM
Standarde Conform EN 55015; Conform EN 61547; Conform EN 61347-2-11
Clasa de protectie III
Tip de protectie IP20
Clasa de eficienta energetica None
DATE LOGISTICE
Interval de temperatura la depozitare -25…85 °C
FIsa DE PRODUS PRIVIND CARACTERISTICILE sI PERFORMANtELE DE MEDIU
Cantitatea de metale pretioase 0 mg
Cantitatea de pamanturi rare 0 mg
Rata minima de material reciclat din ambalaj 80 % 1)
Procentul minim de continut reciclat din produs 0 % 1)
Reciclabilitatea produsului Produs in mare parte reciclabil 1)
Caracterul reciclabil al ambalajului Ambalaje in mare parte reciclabile 1)
Lista substantelor periculoase cuprinse in produs in concentratii mai mari de 0,1% in procent de masa Nu
Contine substante care prezinta motive de ingrijorare deosebita in concentratii mai mari de 0,1% in procent de masa Nu
1) in conformitate cu Decretul AGEC 2022-748 (Legislatia franceza impotriva deseurilor pentru o economie circulara)
Pret: 1.317,40 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/driver-led-ledvance-osram-ot-dmx-rgbw-dim-180-00-w-12-

24-v-ip20-dimabil