



LEDVANCE DISPOZITIV DE CONTROL ILUMINAT LEDVANCE (OSRAM) LUXEYE SENSE DALI BT, 220-240 V, IP20

Beneficii produs Automatic start of light regulation after power-on (out of the box function) Basic functionality without configuration thanks to applied pre-settings Easy and fast customization of important parameter via screwdriver V(?) corrected light sensor element Predefined and customizable configurations for all applications Password protection for user and configuration APP access Easy report generation of all commissioned sensors Easy report sharing via email DEMO Mode usable without device Zone de utilizare Offices Conference rooms Training rooms Corridors Surface mounting via LUXeye SENSE CM KIT Caracteristici produs One DALI broadcast output channel Daylight-dependent regulation and presence-dependent control of light Operation via standard pushbutton Outputs with electronical reversible short-circuit and overload protection Change of delay time with screwdriver direct at the sensor Change of lighting intensity with screwdriver direct at the sensor Halogen free polycarbonate plastic housing Controller with integrated light and presence sensor, DALI output channel Presence detection via passive IR element Light control with app connection via Bluetooth Light control via smart phone Adjustment of all settings via smartphone Individual activation and deactivation of light and presence sensor Function indicator with three color LED Various shutters included for different detection areas Echipamente / Accesorii Suitable for up to 20 electronic control gears Free App for iOS and Android DATE ELECTRICE

Putere nominala 0,40 W

Tensiune nominala 220...240 V

Frecventa retea 50/60 Hz

Dimensiuni si greutate

Lungime 90,00 mm

Latime 90,00 mm

inaltime 81,00 mm

Diametru 95,0 mm

Greutate produs 144,00 g

CULORI si MATERIALE

Culoare produs Alb

Temperaturi si conditii de functionare

Intervalul temperaturii ambientale 0...+55 °C

DATE SUPLIMENTARE REFERITOARE LA PRODUS

Numar de iesiri de control 20

Numar de senzori ce se pot conecta 3

Max. cuplaje/senzori cu butoane ce se pot conecta 3

Punerea in functiune a aplicatiei App (Android/ iOS)

Grupuri 1

Capacitati

Reglabil (cu posibilitate de diminuare a intensitatii luminoase) Nu

Interfata de diminuare a intensitatii luminoase DALI

Protectie impotriva supraincalzirii Da

inaltime maxima de instalare 5 m

Zona de detectie 10 m 1)

Unghi de detectie 110 °

Tip de instalare Integrare in plafon

Intervalul transmitatorului 15 m

Interval de functionare, senzor de lumina 20...5000 lx 2)

1) Diametru pentru detectarea miscarii la o inaltime de instalare de 5 m

2) Aproximativ, masurat la senzor

CERTIFICATE SI STANDARDE

Marci de omologare – aprobare CE

Clasa de protectie II

Tip de protectie IP20

Clasa de eficienta energetica None

FISA DE PRODUS PRIVIND CARACTERISTICILE SI PERFORMANTELE DE MEDIU

Cantitatea de metale pretioase 0 mg

Cantitatea de pamanturi rare 0 mg

Rata minima de material reciclat din ambalaj 80 % 1)

Procentul minim de continut reciclat din produs 0 % 1)

Reciclabilitatea produsului Produs in mare parte reciclabil 1)

Caracterul reciclabil al ambalajului Ambalaje in mare parte reciclabile 1)

Lista substantelor periculoase cuprinse in produs in concentratii mai mari de 0,1% in procent de masa Nu

Contine substante care prezinta motive de ingrijorare deosebita in concentratii mai mari de 0,1% in procent de masa Nu

1) in conformitate cu Decretul AGEC 2022-748 (Legislatia franceza impotriva deseurilor pentru o economie circulara)

Pret: 681,77 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/dispozitiv-de-control-iluminat-ledvance-osram-luxeye-sense-dali-bt-220-240-v-ip20>