Image not found or type



LEDVANCE DRIVER LED LEDVANCE (OSRAM) OT FIT 120/220-240/750 D LT2 L, 120,00 W, 220-240 V, 750 MA, IP20

Beneficii produs Flexible current setting (LEDset2) Lifetime: up to 100,000 h (temperature at T c = 65 °C, max. 10 % failure rate) High quality of light thanks to low output ripple current Very high efficiency Fulfill safety requirement due to overload, overtemperature, Hot Plug protection Zone de utilizare Linear lighting for office, education, industry, storage areas and retail Installation in emergency lighting systems according to IEC 61347-2-13, appendix J Suitable for installation in emergency lighting systems according to EN 60598-2-22 Suitable for luminaires of protection class I Caracteristici produs Line frequency: 0 Hz | 50 Hz | 60 Hz Versatile scope of application due to output power range of up to 120 W Supply voltage: 220…240 V Available with output current range: up to 750 mA Non-isolated drivers DATE ELECTRICE
Putere nominala 120,00 W
Putere nominala de iesire 13.5…120 W
Tensiune nominala 220…240 V
Tensiune nominala de iesire 54…216 V
CA tensiune de intrare 198…264 V
CC tensiune de intrare 176…276 V
U-OUT (tensiune de lucru) < 250 V
Curent nominal de iesire 250…700 mA 1)
soc de curent la anclansare 70 A
Toleranta curent de iesire ±5 %
Curent de ondulatie la iesire (100 Hz) < 1 %
Frecventa retea 0/50/60 Hz
Distorsiune armonica totala < 5 %
Factor de putere ? > 0,99
Eficienta ECG ?93 %
Pierdere de putere a dispozitivului 12 W
Nr. ECG max. pe disjunctor 10 A (B) 8
Nr. ECG max. pe disjunctor 16 A (B) 13

Nr. ECG max. pe disjunctor 25 A (B) -
Capacitate la supratensiune tranzitorie (L/N - impamantare) 2 kV
Capacitate la supratensiune tranzitorie (L-N) 1 kV
Izolatie galvanica Neizolat
Parametru licarire (Pst LM) ?1
1) ±5%
DATE FOTOMETRICE
Parametru licarire (Pst LM) ?1
Parametru efect stroboscop (SVM) ?0.4
Dimensiuni si greutate
Lungime 360,00 mm
Distantare orificiu de montare, lungime 350,0 mm
Latime 30.00 mm
inaltime 21.00 mm
Sectiune transversala de cablu, partea de intrare 0.5…1.5 mm²
Sectiune transversala de cablu, partea de iesire 0.5…1.5 mm²
Lungimea de pregatire a cablului, partea de intrare 8.5…9.5 mm
Lungimea de pregatire a firului, partea de iesire 8.5…9.5 mm
Greutate produs 290,00 g
CULORI sI MATERIALE
Materialul carcasei Metal
Material corp Metal
Temperaturi si conditii de functionare
Intervalul temperaturii ambientale -25…+60 °C
Temperatura maxima in punctul de proba tc 75 °C
Temperatura max. a carcasei in caz de defectiune 110 °C
Umiditate relativa permisa pe durata functionarii 5…85 % 1)
1) Maxim 56 de zile/an la 85 %
Durata de viata
Durata de viata ECG 50000 h; 100000 h 1)
1) La maxim T c = 75°C / 10% rata a defectarii / La T c = 65°C / 10% rata a defectarii
DATE SUPLIMENTARE REFERITOARE LA PRODUS
Capsulat Nu
Capacitati
Reglabil (cu posibilitate de diminuare a intensitatii luminoase) Nu
Protectie impotriva supraincalzirii Reversibil automat
Protectie la supraincarcare Reversibil automat
Protectie la scurtcircuit Reversibil automat
Protectie la sarcina nula Da
Lungime max. a cablului la modulul lampa/LED 2,0 m
Potrivit pentru aparate de iluminat cu clasa de protectie I
Potrivit pentru iluminat de urgenta Da
Tip de conectare, partea de iesire Borna cu apasare
CERTIFICATE sI STANDARDE
Marci de omologare – aprobare CE; EL; VDE-EMC; ENEC 10; CCC; RCM
Standarde Conform EN 61347-1; Conform EN 61347-2-13; Conform EN 62384; Conform EN 61000-3-2; Conform EN 61000-3-3; Conform EN 61547
Clasa de protectie I
Tip de protectie IP20
Clasa de eficienta energetica None
DATE LOGISTICE
Interval de temperatura la depozitare -40…+85 °C
FIsa DE PRODUS PRIVIND CARACTERISTICILE sI PERFORMANtELE DE MEDIU
Cantitatea de metale pretioase 0 mg

Cantitatea de pamanturi rare 0 mg
Rata minima de material reciclat din ambalaj 80 % 1)
Procentul minim de continut reciclat din produs 0 % 1)
Reciclabilitatea produsului Produs in mare parte reciclabil 1)
Caracterul reciclabil al ambalajului Ambalaje in mare parte reciclabile 1)
Lista substantelor periculoase cuprinse in produs in concentratii mai mari de 0,1% in procent de masa Nu
Contine substante care prezinta motive de ingrijorare deosebita in concentratii mai mari de 0,1% in procent de masa Da
Lista substantelor care prezinta motive de ingrijorare deosebita in concentratii mai mari de 0,1% in procente masice Lead (7439-92-1)
1) in conformitate cu Decretul AGEC 2022-748 (Legislatia franceza impotriva deseurilor pentru o economie circulara)
Pret: 121,65 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/driver-led-ledvance-osram-ot-fit-120-220-240-750-d-lt2-l-120-00-w-220-240-v-750-ma-ip20