Image not found or type



LEDVANCE BALAST ELECTRONIC LEDVANCE (OSRAM) PTI 70/220-240 I, 79,00 W, 220-240 V, IP20

Beneficii produs Extended terminal section enables mains looping Screw-down cable clamps for reliable strain relief Long reliable life at maximum permitted temperatures Automatic safety shutdown of lamps in the event of a defect or at end of life (EoL) Zone de utilizare Shop lighting Health and fitness areas (in luminaires with protection class IP66 or higher) Effect and accent lighting Caracteristici produs Energy Efficiency Index EEI: A2 Supply voltage: 220…240 V Line frequency: 50…60 Hz RI suppression: to EN 55015/CISPR 15 Safety: to EN 61347-2-12 Line harmonics according to EN 61000-3-2 Immunity according to EN 61547 Recomandari privind siguranta Caracteristici termice Pierderile de balast si radiatia termica a becului pot determina o acumulare de caldura intr-o carcasa complet inchisa. Prin urmare, trebuie sa va asigurati ca temperatura in punctul de masurare t c al ECG nu depaseste valoarea maxima. Atentie! Din motive de siguranta, inainte de a schimba becul, deconectati dispozitivul! DATE ELECTRICE
Putere nominala 79,00 W
Tensiune nominala 220…240 V
Tensiune nominala de iesire 250 V
CA tensiune de intrare 198…264 V
U-OUT (tensiune de lucru) 250 V
Tip de curent AC
soc de curent la anclansare 45 A 1)
Frecventa retea 50/60 Hz
Factor de putere ? 0,95 2)
Eficienta ECG 92 %
Nr. ECG max. pe disjunctor 10 A (B) 7 3)
Nr. ECG max. pe disjunctor 16 A (B) 13 3)
Frecventa de functionare 0.200…0.240 kHz
1) t latime = 250 µs (masurat la 50% I varf)
2) Minim
3) Tip B

Dimensiuni si greutate
Lungime 171,00 mm
Distantare orificiu de montare, lungime 163,0 mm
Latime 83.00 mm
inaltime 32.00 mm
Sectiune transversala de cablu, partea de intrare 0.75…2.5 mm²
Sectiune transversala de cablu, partea de iesire 0.75…2.5 mm²
Lungimea de pregatire a cablului, partea de intrare 10…11 mm
Lungimea de pregatire a firului, partea de iesire 10…11 mm
Greutate produs 290,00 g
CULORI sI MATERIALE
Materialul carcasei Plastic
Material corp Plastic
Temperaturi si conditii de functionare
Intervalul temperaturii ambientale -25…+50 °C
Temperatura maxima in punctul de proba tc 80 °C
Temperatura max. a carcasei in caz de defectiune 110 °C
Umiditate relativa permisa pe durata functionarii 5…85 % 1)
1) Maxim 56 de zile/an la 85 %
Durata de viata
Durata de viata ECG 50000 h 1)
1) La maxim T c / 10% rata a defectarii
Capacitati
Reglabil (cu posibilitate de diminuare a intensitatii luminoase) Nu
Protectie impotriva supraincalzirii Reducerea puterii si oprirea la T > 80 °C in punctul tc
Lungime max. a cablului la modulul lampa/LED 1.5 m
Potrivit pentru aparate de iluminat cu clasa de protectie I
Potrivit pentru iluminat de urgenta Nu
CERTIFICATE sI STANDARDE
Marci de omologare – aprobare ENEC 10; VDE; VDE-EMC; EAC; C-Tick
Standarde Conform EN 61347-2-12; Conform EN 55015; Conform EN 61000-3-2; Conform EN 61547; Conform EN 62493
Clasa de protectie I
Tip de protectie IP20
Clasa de eficienta energetica A2
EEI– Eticheta energetica A2
DATE LOGISTICE
Interval de temperatura la depozitare -40…+85 °C
FIsa DE PRODUS PRIVIND CARACTERISTICILE sI PERFORMANtELE DE MEDIU
Cantitatea de metale pretioase 0 mg
Cantitatea de pamanturi rare 0 mg
Rata minima de material reciclat din ambalaj 80 % 1)
Procentul minim de continut reciclat din produs 0 % 1)
Reciclabilitatea produsului Produs in mare parte reciclabil 1)
Caracterul reciclabil al ambalajului Ambalaje in mare parte reciclabile 1)
Lista substantelor periculoase cuprinse in produs in concentratii mai mari de 0,1% in procent de masa Nu
Contine substante care prezinta motive de ingrijorare deosebita in concentratii mai mari de 0,1% in procent de masa Da
Lista substantelor care prezinta motive de ingrijorare deosebita in concentratii mai mari de 0,1% in procente masice Lead (7439-92-1)
1) in conformitate cu Decretul AGEC 2022-748 (Legislatia franceza impotriva deseurilor pentru o economie circulara)
Pret: 194,47 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/balast-electronic-ledvance-osram-pti-70-220-240-i-79-00-w-220-240-v-ip20