



GEWISS ESALITE HB - 20K - 60° OPTIC - DALI - 5700 K (CRI 80) - IP65 - CLASS I - RAL 9006 GREY

DATE TEHNICE

Versiuni
5700K lumina rece

Greutate (Kg)
7.5

Optica
60°

Puterea sistemului
148 W

Lumina iesire (lm)

17200

Temperatura de culoare
5700 K (CRI>80)

Flux nominal (lm)
20000

Aplicatie
Interna

Cod IK
IK06

Temperatura de operare
-30 +50 °C

Culoare
Gri RAL 9006

Lampa tip
LED - Neinlocuibil

Tip driver
Driver Led Dali

Curent LED
0.7 A

Seria
ESALITE HB - 20K

Clasa de protectie IP
IP65

Clasa izolatie
I

Tensiune
220/240 V - 50/60 Hz

Clasa de eficienta a LED-urilor integrate
A · A++

Garantie
5 ani

Life time L90B10 (Tq 25°)
100000 h

Overvoltage resistance
Common mode: 8KV; Differential mode: 6KV

Life time L90B10 (Tq 50°)
49000 h

Ecran
Plastic

Electrocod
2444

Pret: 2.666,91 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/esalite-hb-20k-600-optic-dali-5700-k-cri-80-ip65-class-i-ral-9006-grey-45290>