



**GEWISS ESALITE HB - 20K - 30° OPTIC - DALI - 3000 K (CRI 80) - IP66 - CLASS I - RAL 9006 GREY**

DATE TEHNICE

Versiuni  
3000 K lumina calda

Greutate (Kg)  
7.5

Optica  
30°

Puterea sistemului  
148 W

Lumina iesire (lm)

14400

Temperatura de culoare  
3000 K (CRI>80)

Flux nominal (lm)  
18000

Aplicatie  
Intern / Extern

Cod IK  
IK08

Temperatura de operare  
-30 +50 °C

Culoare  
Gri RAL 9006

Lampa tip  
LED - Neinlocuibil

Tip driver  
Driver Led Dali

Curent LED  
0.7 A

Seria  
ESALITE HB - 20K

Clasa de protectie IP  
IP66

Clasa izolatie  
I

Tensiune  
220/240 V - 50/60 Hz

Clasa de eficienta a LED-urilor integrate  
A · A++

Garantie  
5 ani

Life time L90B10 (Tq 25°)  
100000 h

Overvoltage resistance  
Common mode: 8KV; Differential mode: 6KV

Life time L90B10 (Tq 50°)  
49000 h

Ecran  
Sticla calita

Electrocod  
2444

Pret: 2.931,15 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/esalite-hb-20k-300-optic-dali-3000-k-cri-80-ip66-class-i-ral-9006-grey-45293>