



**GEWISS ESALITE HB - 24K - ELLIPTICAL OPTIC - DALI - 4000 K (CRI 80) - IP66 -
CLASS I - RAL 9006 GREY**

DATE TEHNICE

Versiuni
4000K lumina naturala

Greutate (Kg)
11.2

Optica
Eliptic

Puterea sistemului
210 W

Lumina iesire (lm)

22200

Temperatura de culoare
4000 K (CRI>80)

Flux nominal (lm)
29000

Aplicatie
Intern / Extern

Cod IK
IK08

Temperatura de operare
-30 +50 °C

Culoare
Gri RAL 9006

Lampa tip
LED - Neinlocuibil

Tip driver
Driver Led Dali

Curent LED
0.9 A

Seria
ESALITE HB - 24K

Clasa de protectie IP
IP66

Clasa izolatie
I

Tensiune
220/240 V - 50/60 Hz

Clasa de eficienta a LED-urilor integrate
A · A++

Garantie
5 ani

Life time L90B10 (Tq 25°)
100000 h

Overvoltage resistance
Common mode: 8KV; Differential mode: 6KV

Life time L90B10 (Tq 50°)
44000 h

Ecran
Sticla calita

Electrocod
2444

Pret: 3.908,28 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/esalite-hb-24k-elliptical-optic-dali-4000-k-cri-80-ip66-class-i-ral-9006-grey-45323>