



SCHRACK LNB TWIN PENTRU 2 RECEIVERE,D40MM

EAN-Code 9004840083859 Lungime 125,00mm Latime neta 85,00mm Inaltime 75,00mm Masa neta 0,26kg. Temperatura minima a mediului ambiant -30°C Temperatura maxima a mediului ambiant 60°C Feed diameter 40mm Receiving from DVB-S and DVB-S2 signals (HDTV compatible) Conexiune F- contacts nickel plated Numar de iesiri 2 Extendable weather protection cap yes Input Frequency Range Low Band - 10.7 - 11.7 GHz High Band - 11.7 - 12.75 GHz Output Frequency Range Low Band - 950 ~ 1950 MHz High Band - 1100 ~ 2150 MHz Oscillation frequency Low Band - 9,75 GHz $\pm 1,5$ MHz High Band - 10.60 GHz ± 1.5 MHz Noise Figure Low Band - ≤ 1.0 dB High Band - ≤ 1.0 dB Cross Polar Isolation 20 dB (Min.) Gain 55 ~ 70dB (Typical) Linearity of gain ± 0.5 dB / 27 MHz Reflector Type Offset L.O. Phase Noise 100 dBc / Hz (@ 100kHz) 50 dBc / Hz (@ 1kHz) 75 dBc / Hz (@ 10kHz) Image Rejection 45 dB (min). Output VSWR(Ref. to 75I $\odot$) 2.5 : 1 (max.) Output Connector Type 75I $\odot$ F-Connector Polarization Control Voltage Range 11.5 ~ 14.0 V (Vertical Polarisation) 16.0 ~ 19.0 V (Horizontal Polarization) Continuous 22 kHz ± 4 kHz (High Band Selection) Produs LNB-uri
Pret: 101,82 LEI (TVA inclus)

Detalii online: <https://www.materialeelectric.ro/lnb-twin-pentru-2-receivere-d40mm-84014>