



SCHRACK MODUL RJ45 ECRANAT, CLASA EA 10GB POE+, PERFORMANCE LINE

EAN-Code 9004840566444 Lungime 36,50mm Latime neta 14,50mm Inaltime 20,80mm Masa neta 0,03kg. Temperatura minima a mediului ambiant -40°C Temperatura maxima a mediului ambiant 70°C Produs Modul conector Ecranaj ecranat Format SCHRACK SFB Conector standard IEC 60603-7-51 Categorie Cat.6a/10GB Class E_A acc. to ISO/IEC 11801 Amendment 1/2 typical link length > 2m, in combination with a CP-cable: CP-Link typ. > 10m 10GbE is supported PoE+ Da Cicluri de conectare %∞ 750 Insertion force %∞ 30N Conductor diameter solid 0,51-0,65mm AWG24/1 - AWG 22/1 Insulation diameter 5 - 9mm Reusable (Module) %∞ 5 cycles with the same diameter RoHS Conform cu directiva EU 2002/95/EC Housing Zinc diecast Strain-relief sliver Zinc diecast Surface nickel plated Shield spring Stainless steel PCB FR4 PCB finish HAL lead-free Material contacte Spring steel Contact finish 0,762 μm / 30 μin Au Insulation housing PA black (RAL9005) Contact support plate PC yellow (RAL1021) Dust protection cover PC clear IDC CuNi2Si IDC finish min. 3-6 μm (120-240μin) Sn Particularte ingress IP2X Water ingress IPX0 Impachetare Bio-degradable Contact resistance %∞ 20m,,| Rezistenta izolatie %∞ 500 M,,| Votage proof - contact-contac %∞ 1000 (DC)V Current carrying capacity at 50°C 1,25A Transfer Impedance @ 1 MHz = %∞ 100m,,| @ 10 MHz = %∞ 200m,,| @ 80 MHz = %∞ 1600m,,| Porturi 1 Pret: 23,53 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/modul-rj45-ecranat-clasa-ea-10gb-poe-performance-line-84080>