



### SCHNEIDER SEPARATOR DE SARCINA COMPACT NSX400NA - 400 A - 3 POLI

<b>range</b>	ComPacT new generation
<b>product name</b>	ComPacT NSX new generation
<b>product or component type</b>	Switch disconnecter
<b>device short name</b>	NSX400NA
<b>poles description</b>	3P
<b>network type</b>	AC
<b>[Ue] rated operational voltage</b>	690 V AC 50/60 Hz conforming to IEC 60947-3
<b>[Ie] rated operational current</b>	AC-22A: 400 A AC 50/60 Hz 220...690 V AC-23A: 400 A AC 50/60 Hz 220...690 V
<b>[Ui] rated insulation voltage</b>	800 V AC 50/60 Hz conforming to IEC 60947-3
<b>[Uimp] rated impulse withstand voltage</b>	8 kV conforming to IEC 60947-3
<b>[Ith] conventional free air thermal current</b>	400 A at 60 °C
<b>[Icm] rated short-circuit making capacity</b>	330 kA with upstream protection circuit breaker 7.1 kA switch-disconnector alone
<b>breaking capacity code</b>	NA
<b>suitability for isolation</b>	Yes conforming to EN/IEC 60947-3
<b>contact position indicator</b>	Yes
<b>visible break</b>	No
<b>utilisation category</b>	AC-22A AC-23A
<b>control type</b>	Complementary Toggle
<b>mounting mode</b>	Fixed
<b>mounting support</b>	Backplate

<b>upside connection</b>	Front
<b>downside connection</b>	Front
<b>[Icw] rated short-time withstand current</b>	1.93 kA during 20 s conforming to IEC 60947-3 5 kA during 1 s conforming to IEC 60947-3 5 kA during 3 s conforming to IEC 60947-3
<b>mechanical durability</b>	15000 cycles conforming to IEC 60947-3 AC-22A: 10000 cycles 440 V AC 50/60 Hz In/2 conforming to IEC 60947-3 AC-22A: 2500 cycles 690 V AC 50/60 Hz In conforming to IEC 60947-3 AC-22A: 5000 cycles 440 V AC 50/60 Hz In conforming to IEC 60947-3 AC-22A: 5000 cycles 690 V AC 50/60 Hz In/2 conforming to IEC 60947-3
<b>electrical durability</b>	AC-23A: 10000 cycles 440 V AC 50/60 Hz In/2 conforming to IEC 60947-3 AC-23A: 2500 cycles 690 V AC 50/60 Hz In conforming to IEC 60947-3 AC-23A: 5000 cycles 440 V AC 50/60 Hz In conforming to IEC 60947-3 AC-23A: 5000 cycles 690 V AC 50/60 Hz In/2 conforming to IEC 60947-3
<b>connection pitch</b>	45 mm
<b>height</b>	255 mm
<b>width</b>	140 mm
<b>depth</b>	110 mm
<b>net weight</b>	5.2 kg
<b>compatibility code</b>	NSX400
<b>standards</b>	Environment EN/IEC 60947 UL 508
<b>product certifications</b>	EAC CCC
<b>IP degree of protection</b>	IP40 conforming to IEC 60529
<b>IK degree of protection</b>	IK07 conforming to IEC 62262
<b>electrical shock protection class</b>	Class II
<b>pollution degree</b>	3 conforming to IEC 60664-1
<b>ambient air temperature for operation</b>	-25...70 °C
<b>ambient air temperature for storage</b>	-50...85 °C

#### Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Weight</b>	5.333 kg
<b>Package 1 Height</b>	15 cm
<b>Package 1 width</b>	16 cm
<b>Package 1 Length</b>	29.5 cm
<b>Unit Type of Package 2</b>	S04
<b>Number of Units in Package 2</b>	2
<b>Package 2 Weight</b>	11.369 kg

<b>Package 2 Height</b>	30 cm
<b>Package 2 width</b>	40 cm
<b>Package 2 Length</b>	60 cm

Pret: 3.297,39 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/separator-de-sarcina-compact-nsx400na-400-a-3-poli-97484>