
www. MATERIALE ELECTRICE .ro
Consiliere specializata

Schneider Electric



SCHNEIDER EASY UPS 3S 30 KVA 400 V 3:1 UPS WITH INTERNAL BATTERIES - 9 MINUTES RUNTIME

Descriere High-efficiency 3-phase UPS with internal batteries providing a runtime of 9 minutes. The UPS features advanced product features, competitive specifications, and robust electrical design, making business continuity easy in the data center or electrical room. This is an exceptionally easy to install, operate, maintain, and service 30 kVA UPS, ideal for small and medium businesses. Includes dust filter and conformance-coated boards for harsh environments
Denumire model Easy UPS 3S 30 kVA 400 V 3:1 UPS with internal batteries - 9 minutes runtime
Include Filtru de praf , Ghid de instalare
, ,
Capacitate putere de iesire 30.0 KW / 30.0 kVA
Putere max. configurabila (wati) 30.0 KW / 30.0 kVA
Tensiune nominala la iesire 230V
Distorsiune tensiune de iesire Sub 3%
Frecventa de iesire (sincronizata cu alimentarea de la retea) 50 Hz , 60 Hz
Alte tensiuni de iesire 220, 240V
Factor de varf 3 : 1
Online cu dubla conversie
Toleranta tensiune de iesire +/- 1.5%
Tensiune de iesire THD Tensiune nominala de intrare 400 3 Faz
Frecventa de intrare 45 - 65 Hz
Interval tensiune de intrare pentru operatii principale 304 - 477 V
Alte tensiuni la intrare 380 , 415
Curent maxim de intrare 55 A
Distorsiune armonica totala de intrare Sub 5% pentru capacitate maxima
Tip de protectie necesara la intrare Switch and fuse
Tip de acumulator VRLA

Module baterie incluse 2
Battery Slots Empty 2
Nota suport baterie de schimb UPS weight does not include battery weight.
Tensiune nominala baterie 240 V
Terminare descarcare tensiune baterie +/-198 VDC
Terminare descarcare curent maxim baterie 81 A
Port(uri) interfata E3S_Parallel , E3S_TempSensor
Inaltime maxima 1400.0 mm
Latime maxima 500.0 mm
Adancime maxima 996.0 mm
Greutate neta 212.0 kg
Greutate de transport 213.0 kg
Inaltime transport 1640.0 mm
Latime de transport 683.0 mm
Adancime transport 1114.0 mm
Culoare Alb
Mediu de operare 0 - 40 °C
Umiditate relativa de functionare 0 - 95 (non-condensing) %
Inaltime de operare 0-984.3 metri
Temperatura de depozitare -15 - 40 °C
Umiditate relativa depozitare 0 - 95 (non-condensing) %
Inaltime depozitare 0-15000 metri
Zgomot sonor la 1 metru de suprafata unitatii 63.000 dB
Pierdere termica online 1810.000 BTU/h
Clasa de protectie IP 20
Aprobari reglementare CE , EAC , IEC 62040-1-1 , IEC 62040-2 , IEC 62040-3 , IEC 62040-4 , ISTA 2B , RCM , WEEE
Garantie standard 1 an reparatii sau inlocuire pe loc cu pornire autorizata din fabrica
RoHS (Restrictionarea substantelor periculoase) Conformitate
Regulament REACH REGULAMENT: Nu contine SVHC (Substante care prezinta motive de ingrijorare deosebita)
Pret: 0,00 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/easy-ups-3s-30-kva-400-v-3-1-ups-with-internal-batteries-9-minutes-runtime-98162